

DHI-SCP3044A-BZ

4-Wire Hybrid Smart Control Panel



Functions

Smart Control Panel

Features multiple functions such as video intercom, video monitoring and wireless alarm. Its Android 14 system supports the installation of APK files, allowing for the expansion of third-party applications.

Scene

It is ideal for villas, communities, apartments and hotels, and is well suited for offices.

Taskwical Cassification			
Technical Specification			
System			
Main Processor	Embedded Processor		
Operating System	Android 14		
Network Protocol	IPv4;RTSP;UDP;DNS;FTP;RTP;TCP;SIP		
Basic			
Screen Type	Capacitive Touchscreen		
Display Screen	10.1-inch display screen		
Screen Resolution	1280 (H) × 800 (V)		
Audio Compression	G.711a; G.711u; PCM		
Audio Input	1 channel		
Audio Output	Built-in speaker		
Audio Mode	Two-way audio		
Audio Enhancement	Echo suppression/digital noise reduction		
Audio Bit Rate	16 kHz, 16 bit		
Function			
Communication Mode	Full digital		

- Adopts the Android 14 system, offering advanced performance and a user-friendly experience.
- Featuring a sleek full-screen design with an ultra-narrow black border, this device combines style and minimalism for an exceptional visual experience.
- With its 10.1-inch IPS capacitive touchscreen and multi-touch technology, the screen offers wide viewing angles of up to 80 degrees both horizontally and vertically, significantly enhancing work efficiency and operational flexibility.
- Supports multiple communication modes including IP, Wi-Fi and IP four-wire.
- Includes multi-color indicators that feature the breathing light function to keep you updated on status changes.
- Wakes up automatically when a person approaches for a seamless experience.
- Equipped with a built-in light sensor, the device automatically adjusts the screen brightness for comfortable viewing.
- With its built-in temperature and humidity detectors, you can
 effortlessly monitor the conditions in your house at any time
 straight from the home screen.


Information Release	Receive and view the published information from the management center	
Elevator Control	Residents can call the elevator through this device to their floor.	
Leave Videos	Yes (SD card is inserted in the indoor monitor or door station)	
DND Mode	Do not disturb period can be set	
Number of Extensions	Villa: 1 main VTH and 9 extensions Apartment: 1 main VTH and 4 extensions	
Expansion Module	ZigBee module Wireless 868 MHz Sensor Bluetooth module	
Storage	Supports micro SD card storage (up to 512 GB)	
Network		
Wi-Fi	Yes	
Wireless Standard	IEEE 802.11a/b/g/n/ac/ax	
Wireless Frequency Range	2.4 GHz; 5 GHz	
Port		
RS-485	1	
USB	1	

DHI-SCP3044A-BZ


Alarm Input	8 channels	
Alarm Output	1 channel	
Power Output	1 port (12 V, 200 mA)	
Door Bell	Yes (use the alarm input port)	
Network Port	$1 \times 10/100$ Mbps Ethernet port	
4-wire	1	
Performance		
Casing Material	PC + ABS	
General		
Appearance Color	Gray	
Power Supply	12 VDC, 2 A Standard PoE	
Power Adapter	Optional	
Installation	Flush Mount	
Certifications	CE	
Accessory	Included: RS-485 and power output cable, bracket and alarm cable. Optional: Power cord	
Accessory Product Dimensions	alarm cable.	
·	alarm cable. Optional: Power cord $246.5~\text{mm}\times156.1~\text{mm}\times33.0~\text{mm}~(9.70"\times6.15"\times$	
Product Dimensions	alarm cable. Optional: Power cord $246.5~\text{mm}\times156.1~\text{mm}\times33.0~\text{mm}~(9.70"\times6.15"\times1.30")~(\text{H}\times\text{W}\times\text{D})$	
Product Dimensions Operating Temperature	alarm cable. Optional: Power cord $246.5 \text{ mm} \times 156.1 \text{ mm} \times 33.0 \text{ mm} \ (9.70" \times 6.15" \times 1.30") \ (H \times W \times D)$ $-10 \text{ °C to } +55 \text{ °C } \ (+14 \text{ °F to } +131 \text{ °F})$	
Product Dimensions Operating Temperature Operating Humidity	alarm cable. Optional: Power cord $ 246.5 \text{ mm} \times 156.1 \text{ mm} \times 33.0 \text{ mm} (9.70" \times 6.15" \times 1.30") (H \times W \times D) $ $ -10 \text{ °C to +55 °C (+14 °F to +131 °F) } $ $ 10\%-95\% \text{ (RH), non-condensing } $	
Product Dimensions Operating Temperature Operating Humidity Operating Altitude	alarm cable. Optional: Power cord 246.5 mm × 156.1 mm × 33.0 mm (9.70" × 6.15" × 1.30") (H × W × D) -10 °C to +55 °C (+14 °F to +131 °F) 10%–95% (RH), non-condensing Below 3,000 m (9,842.52 ft)	
Product Dimensions Operating Temperature Operating Humidity Operating Altitude Power Consumption	alarm cable. Optional: Power cord 246.5 mm × 156.1 mm × 33.0 mm (9.70" × 6.15" × 1.30") (H × W × D) -10 °C to +55 °C (+14 °F to +131 °F) 10%–95% (RH), non-condensing Below 3,000 m (9,842.52 ft) ≤ 12 W (standby), ≤ 15 W (working)	
Product Dimensions Operating Temperature Operating Humidity Operating Altitude Power Consumption Gross Weight	alarm cable. Optional: Power cord $ 246.5 \text{ mm} \times 156.1 \text{ mm} \times 33.0 \text{ mm} (9.70" \times 6.15" \times 1.30") (H \times W \times D) $ $ -10 \text{ °C to +55 °C (+14 °F to +131 °F) } $ $ 10\%-95\% (RH), \text{ non-condensing } $ $ \text{Below 3,000 m (9,842.52 ft) } $ $ \leq 12 \text{ W (standby),} \leq 15 \text{ W (working) } $ $ 1,291 \text{ g } (2.85 \text{ lb) } $	

Ordering Information				
Туре	Model	Description		
Smart Control Panel	DHI-SCP3044A-BZ	4-Wire Hybrid Smart Control Panel		

Installation



Dimensions (mm[inch])



Application

